

PCTWORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : A61M 5/20 // 5/31		A1	(11) International Publication Number: WO 98/01170
			(43) International Publication Date: 15 January 1998 (15.01.98)
(21) International Application Number: PCT/DK97/00256		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 12 June 1997 (12.06.97)		Published With international search report.	
(30) Priority Data: 0751/96 5 July 1996 (05.07.96) DK			
(71) Applicant (for all designated States except US): NOVO NORDISK A/S [DK/DK]; Novo Allé, DK-2880 Bagsværd (DK).			
(72) Inventor; and (75) Inventor/Applicant (for US only): HANSEN, Niels-Aage [DK/DK]; Svenstrupvang 3, DK-4622 Havdrup (DK).			
(74) Common Representative: NOVO NORDISK A/S; Corporate Patents, Novo Allé, DK-2880 Bagsværd (DK).			

(54) Title: AUTOMATIC NEEDLE INSERTION MECHANISM

(57) Abstract

An automatic needle insertion device for a pen shaped syringe comprising a cartridge holder (2) wherein a cartridge with a drug can be accommodated, and a dose setting and injection part (1) by which a wanted dose may be set and subsequently pressed out from the cartridge by pressing a button (12) projecting from the dose setting and injection part (1). The device comprises a mainly tubular housing (31) in which a tubular pen holder (22) in which a pen can be mounted can be axially displaced in a proximal direction to cock a spring (30) which can thereafter be released to drive the pen holder (22) with the pen a set distance in a distal direction.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LJ	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Automatic needle insertion mechanism

The invention relates to automatic needle insertion mechanisms for pen shaped
5 syringes comprising a cartridge holder wherein a cartridge with a drug can be
accommodated, and a dose setting and injection part by which a wanted dose
may be set and subsequently pressed out from the cartridge by pressing a button
projecting from the dose setting and injection part. As it will be understood the
dose setting and injection part forms the more mechanically complicated part of
10 the syringe whereas the cartridge holder is a rather simple tubular part. The
designation "pen shaped" shall be taken broadly recognising that a pen need not
be oblong and have a circular cross section. Syringes designed to apportion a
number of set doses from an ampoule and commonly carried by the user are often
called pens even when they do not have a shape making them look like a fountain
15 pen as had the first syringes of that kind.

Pen syringes are mainly used by patients to perform self injections. By such
handling by non professionals it is important that the handling is simple so that
complications are avoided. A phase of the injection upon which most people look
20 at with disinclination is the needle insertion phase. This disinclination may incur
that the needle insertion is not performed as purposefully quickly as it is
appropriate to obtain a precise, uncomplicated and painless insertion.

Consequently different apparatus for automatic needle insertion has been
25 proposed. US 4 787 891 describes an injection apparatus for common single dose
syringes. In this apparatus the syringe is mounted in a holder which against the
force of a spring may be drawn into a barrel and locked in its retracted position.
When the barrel is placed where the needle insertion is wanted and the lock is
released, the holder with the syringe is forced forwards by the spring and a needle
30 mounted on the syringe will project from the end of the barrel and pierce the skin
where the barrel is placed.

From WO 88/08725 a pen shaped syringe is known wherein an automatic needle
insert mechanism is integrated. The spring which provides the force necessary to
35 insert the needle is further used to inject a set dose of medicine from the ampoule in
the pen syringe. However, users may prefer to perform the injection themselves as
this offers a possibility of adjusting the injection speed in accordance with the
receiving ability of the tissue so that tensions and infiltrations are avoided.

Also pen shaped syringes with integrated needle insertion mechanisms but without automatic injection are known. Consequently, it is possible to buy pen syringes with built in needle insertion mechanisms.

5

If one has a pen syringe without such a mechanism, it will be attractive to have a separate needle insertion mechanism in which a pen shaped syringe may be mounted. This will give the user a freedom to the extent he may want to sometimes use a pen with and sometimes a pen without an automatic needle
10 insertion mechanism.

The object of the invention is to provide such an automatic needle insertion mechanism for a syringes by which more individually set doses may be apportioned from a cylinder ampoule which can be changed when empty.

15

This is obtained by a pen shaped syringe of the kind described in the opening of this application, which syringe is according to the invention characterised in that the device comprises a mainly tubular housing in which a tubular pen holder in which a pen can be mounted can be axially displaced in a proximal direction to
20 cock a spring which can thereafter be released to drive the pen holder with the pen a set distance in a distal direction. It shall be noticed that the designation "tubular" do not necessarily involve a tube having a circular cross section, the tube may have any appropriate cross section, e. g. a rectangular cross section.

25 In an appropriate embodiment of the invention the pen holder is shaped as a cartridge holder and only the dose setting and injection part of the pen syringe is mounted in the pen holder.

The cartridge holder forms a simple and inexpensive part of the pen syringe
30 which part is designed to be in a simple way dismantled from the syringe when a new cartridge is going to be mounted. A cartridge holder with an automatic needle insertion mechanism can be seen as a spare part which can replace the common cartridge holder. If later a syringe without auto insertion device is wanted, the cartridge holder may again be replaced by the original simple one.

35

In a further appropriate embodiment of the mechanism according to the invention the cartridge holder shaped pen holder may at a proximal end have an inner thread in which an outer thread of the dose setting and injection part of a pen may

be received.

According to the invention the pen holder may be provided with inspection windows to allow the same inspections as do a common cartridge holder. This way
5 confusion of a user who is familiar with the pen with the original cartridge holder is avoided. It is an advantage that the means for operating the needle insertion device are firmly connected with the pen holder so that no superfluous operating means are left on the pen syringe when the pen holder with the automatic needle insertion device is replaced by the original cartridge holder.

10

According to an embodiment of the invention the distal end of the tubular housing of the automatic needle insertion device may be obliquely cut to allow abutment against the skin at an angle so that the needle may be inserted at an angle of about 45°.

15

In the following the needle insertion mechanism according to the invention will be described with reference to the drawing, wherein

20 Figure 1 shows a common known pen shaped syringe for the delivery set doses of medicine from a cartridge,

Figure 2 shows a sectional view of an automatic needle insertion device with a cartridge holder shaped pen holder.

25 Figure 3 shows a pen shaped syringe mounted with the pen holder shown in figure 2, with the needle insertion mechanism uncocked, and

Figure 4 the device in figure 3 with the needle insertion mechanism cocked.

30

Figure 1 shows schematically a pen shaped syringe for injection of set doses of medicine from a cartridge. The syringe consists of a dose setting part 1 comprising a housing containing a dose setting mechanism in which an intended dose may be set by turning a dose setting knob 12. During the setting of the dose the knob 12 is
35 elevated from the housing 11 a distance proportional with the size of the dose set. When the knob 12 is pressed back to abutment with the housing, a piston rod 13 extending from the housing will be driven further out from the end of the housing opposite the knob 12 another distance proportional with the set dose. An external

thread 14 at the end of the housing from which the piston rod projects serves the connection of said housing with a cartridge holder 2.

The cartridge holder 2 has at an end 21 an internal thread for the receipt of the external thread 14 of the dose setting part 1. The cartridge holder 2 has a tubular body 22 wherein a cartridge of the kind which is at an output end closed by a rubber membrane and at the other end closed by a piston may be accommodated with its piston facing the end 21 of the cartridge holder 2. Cut-outs 23 in the wall of the body enables inspection of the not shown cartridge mounted in the holder. The remaining wall of the body is provided with marks 25 indicating how much medicine is left in the cartridge when the piston reach the respective marks. A further inspection window 24 near the end of the cartridge makes it possible to inspect the output end of the cartridge to see whether the cartridge is emptied to an extent that calls for a change of said cartridge.

15

A cap 3 can cover the cartridge holder and a possible injection needle mounted at the output end of the cartridge so that the pen may be kept free from dust and the needle is protected.

Figure 2 shows a sectional view of a cartridge holder into which a needle insertion mechanism is integrated. Details corresponding to details in the cartridge holder 2 shown in figure 1 is given the same reference numbers. This goes for the body 22 which however is supplied with an elongation 26 and a collar 27, the marks 25, the inspection window 24 and the end 21 in which further an internal thread 28 is seen.

The cartridge holder body is enclosed by two shells which are joined together along their edges to form a housing 31 in which the cartridge holder body is mounted axially displaceable. Between an inward projection 29 in the housing and the collar 27 surrounding the cartridge holder body a helical spring 30 is mounted surrounding the end of the cartridge holder which carries the internal thread 22 for reception of a dose setting part 1. When the cartridge holder body 22 with its elongation is drawn upwards in the housing 31 in figure 2, the helical spring is compressed and when the body is drawn so far that a spring ring 32 can engage an opening 33 near the upper end of the housing, the cartridge holder body will be held in a cocked position from which it may be released by pressing a trigger button 34 at the upper end of the housing 31.

One of the shells forming the housing has at its lower end in figure 2 a rest piece 35 which may be placed resting against the skin where an injection is going to be made whereas the lower end of the other shell is without such a rest so that an opening between the skin and the end of the housing is formed for inspection of
5 the needle in its position ready for insertion perpendicularly to the skin. Alternatively the fact that the resting piece lacks on one of the shells allows that the syringe is held with the rest piece of one shell and the edge of the shell which has no rest piece in abutment with the skin so that the needle pierces the skin at an angle of about 45°. The lower end of the housing is closed by a protective cap
10 36 when the device is not in use.

Figure 3 shows a dose setting part 1 of a pen shaped syringe mounted with a cartridge holder wherein a needle insertion mechanism is integrated. The dose setting part 1 has its external thread 14 screwed into the internal thread 28 of the
15 cartridge holder. The dose setting part which project over the end of the cartridge holder housing forms a good grip by which the cartridge holder body 22 may be drawn upwards in the housing in figure 3 to compress the spring 30 between the collar 27 of the cartridge holder body and the inward projection 29 of the housing 31. In the uncocked condition of the device the needle will project beyond the rest
20 piece 35 whereas the needle in the cocked condition of the device as shown in figure 4 will be retracted a short distance behind the outer end of the rest piece.

CLAIMS

1. An automatic needle insertion device for a pen shaped syringe comprising a cartridge holder wherein a cartridge with a drug can be accommodated, and a
5 dose setting and injection part by which a wanted dose may be set an subsequently pressed out from the cartridge by pressing a button projecting from the dose setting and injection part, characterised in that the device comprises a mainly tubular housing in which a tubular pen holder in which a pen can be mounted can be axially displaced in a proximal direction to cock a spring which
10 can thereafter be released to drive the pen holder with the pen a set distance in a distal direction.
2. A device according to claim 1, characterised in that the pen holder is shaped as a cartridge holder and only the dose setting and injection part of the pen syringe
15 is mounted in the pen holder.
3. A device according to claim 2, characterised in that the pen holder has at a proximal end an inner thread in which the outer thread of a dose setting and injection part can be received.
20
4. A device according to anyone of the preceding claims, characterised in that the pen holder has inspection windows has inspection windows allowing the same inspections as a common cartridge holder.
- 25 5. A device according to anyone of the preceding claims, characterised in that the tubular housing at its distal end is obliquely cut.

1/2




Fig. 1




Fig. 2

2/2




Fig. 3




Fig. 4

INTERNATIONAL SEARCH REPORT

1

International application No.

PCT/DK 97/00256

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: A61M 5/20 // A61M 5/31

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5282793 A (ELDON E. LARSON), 1 February 1994 (01.02.94), column 1, line 27 - line 56, figure 3	1-3
Y	--	4,5
X	DE 3241911 A1 (KIRCHNER, GEORG), 17 May 1984 (17.05.84), page 11, line 19 - page 12, line 8, figure 1	1-3
Y	--	4,5
Y	US 4850973 A (PAVEL JORDAN ET AL), 25 July 1989 (25.07.89), figure 3	4
	--	

☒ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

Z document member of the same patent family

Date of the actual completion of the international search

3 October 1997

Date of mailing of the international search report

16-10-1997

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

May Hallne
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/DK 97/00256

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0388169 A2 (EASTMAN KODAK COMPANY), 19 Sept 1990 (19.09.90), figure 14 -- -----	5

INTERNATIONAL SEARCH REPORT
Information on patent family members

01/09/97

International application No.
PCT/DK 97/00256

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
US	5282793	A	01/02/94	NONE	
DE	3241911	A1	17/05/84	NONE	
US	4850973	A	25/07/89	NONE	
EP	0388169	A2	19/09/90	CA 1337167 A	03/10/95
				JP 3000077 A	07/01/91
				US 5070884 A	10/12/91
				US 5193552 A	16/03/93
				CA 1332164 A	27/09/94
				EP 0389167 A	26/09/90
				JP 2284657 A	22/11/90
				US 5007892 A	16/04/91
				CA 2013021 A,C	29/05/91
				CA 2024891 A,C	30/05/91
				CA 2024892 A,C	30/05/91
				CA 2029459 A	30/05/91
				EP 0430355 A	05/06/91
				EP 0430356 A	05/06/91
				JP 3185356 A	13/08/91
				JP 3270748 A	02/12/91
				US 5032288 A	16/07/91